



LOKI

Bendable for mounting on flat or curved surfaces

USER GUIDE

1.Product Description


LOKI silicone bendable LED light has effective resistance to impact and corrosion. It can bend backward up to 30°. Better anti-vellowing and antioxidant lens design than traditional ones. 3M VHB tape mounting and screw mounting.

2.Technical Specifications

Product Name	LOKI	
Max Power	10W	
Voltage	DC 10-33V	
Flash Pattern	Single 19/ Dual 12	
IP Rating	IP67+IP69K	
Operating Temperature	-30°C to +70°C	
Dimensions	100*23*10mm(Bezel-Free)	
Certifications	ECE R65 Class 1, ECE R10, SAE J595, T13	

3.Product Introduction

3.1. Dimensions



3.2. Wirings

A. Function Wiring

Single Color



- . Flash paterns will be reset when YELLOW wires are connected to RED wire for more than 5 seconds

WHITE — Alternation Flash

. With the power off.connect the WHITE wire from one lighthead to + VDC and leave the other unconnected. Their patterns will alternate when the lightheads are actived.

Dual Color




- To change flash patterns, apply +VDC for less than 5 second and release.
- . Flash paterns will be reset when YELLOW wires are connected to RED wire for more than 5 seconds.

WHITE — Alternation Flash


. With the power off,connect the WHITE wire from one lighthead to + VDC and leave the other unconnected. Their patterns will alternate when the lightheads are actived.

B. Products Wiring

Pattern Synchronization



Pattern Alternation



C. Color Sheet of Wire and LED

Dual Color


LED Combinations WIRE	RED	BROWN
024118TAW	w	A
024118TBW	w	В
024118TRW	w	R
024118TAR	A	R
024118TAB	А	В
024118TBR	R	В

4. Mounting

A. Screw Mounting With Included Bezel



B. 3M VHB Tape Mounting



A Warning

