

mpower® Fascia 4x2 Light



Bright, flexible, available in hundreds of configurations



Stud Mount



Quick Mount



Screw Mount

FEATURES



- Single, dual or tricolor capabilities
- Patented, silicone-molded one-piece housing and optic design delivers advantages over conventional polycarbonate lenses
- Compatible with the ConfigureIT system for easy light programming
- Great resistance to gravel pitting, scratching and cracking
- Superior sealing to prevent water from entering light
- High UV and thermal stability to prevent lens from yellowing over time
- Small footprint with maximum candela output

SPECIFICATIONS

Input Voltage Range	9-32 Vdc
Operating Temperature	-30°C to +85°C
LED Color Capabilities	Single, dual, tricolor
LED Color Options	● ● ● ● ○
LED Count	Single - 12 & 16 LEDs, Dual - 24 LEDs, Tricolor - 36 LEDs
Flash Patterns	15
Light Sync	Up to 24 lightheads (Sync 2)
Dimensions	Screw mount: 4.53" L x 1.5" H x 0.43" D (11.5 cm L x 3.8 cm H x 1.09 cm D) Stud mount: 4.07" L x 1.5" H x 0.43" D (10.34 cm L x 3.8 cm H x 1.09 cm D) Quick mount: 4.07" L x 1.5" H x 0.47" D (10.34 cm L x 3.8 cm H x 1.19 cm D)
Mount Types	Stud, quick or screw mount
Certifications	SAE J595, SAE J845, CA Title 13, NFPA 1901

PART NUMBERS

Quick Mount

12 LED, Single Color	EMPSA05BN-(x)
16 LED, Single Color	EMPSA05BS-(x)
24 LED, Dual Color	EMPSA05BT-(x)
36 LED, Tricolor	EMPSA05BU-(z)

Stud Mount

12 LED, Single Color	EMPSA05C0-(x)
16 LED, Single Color	EMPSA05C1-(x)
24 LED, Dual Color	EMPSA05C2-(x)
36 LED, Tricolor	EMPSA05C3-(z)

Screw Mount

12 LED, Single Color	EMPSA05BW-(x)
16 LED, Single Color	EMPSA05BX-(x)
24 LED, Dual Color	EMPSA05BY-(x)
36 LED, Tricolor	EMPSA05BZ-(z)

Single Colors (x) A= ● B= ● R= ● W= ○ G= ●
Dual Colors (x) D= ●○ E= ●○ F= ●○ H= ●○ J= ●●

Tricolors (z) 6= ●●● 8= ●●○

